



Focal length: 18mm Exposure: F/5.6 1/125 sec ISO400 © Thomas Kettner



Focal length: 18mm Exposure: F/3.5 1/40 sec ISO800 © Thomas Kettner

Covering focal lengths from 18 to 200mm, this compact zoom can take great shots in a myriad of situations.

Tamron introduces a lens made for capturing everyday life and special occasions with a smile. The 18-200mm VC is the culmination of our persistent efforts to perfect the high-power zoom lens category since 1992. This innovative lens is lightweight, high quality and ideal as a beginner's first interchangeable lens — or a casual user's **only** lens.



World's lightest at 400g. (14.1 oz.)

Comfortable to carry—even all day.

New high-performance AF drive module.

A newly designed autofocus drive module with optimal DC motor-gear train integration makes AF faster, quieter and more precise.

Frame shots instantly – no need to change lenses.

Covers the zoom range you need for everyday shots, providing the flexibility to take group photos in tight spaces or make distant subjects appear closer—all with just one lens.

VC (Vibration Compensation) for sharp handheld shooting.

Shoot handheld in situations where others need a tripod. Telephoto and night shots are prone to camera shake, but VC works to keep photos sharp and clear.




Focal length: 200mm Exposure: F/11 1/20 sec

For more information about the B018, please visit the B018 Special Website ▶▶▶ www.tamron.co.jp/en/lineup/b018/

18-200mm F/3.5-6.3 Di II VC for Canon, Nikon 18-200mm F/3.5-6.3 Di II for Sony Model: B018

Model	B018	Maximum Diameter	Φ75mm
Focal Length	18-200mm	Length*1	for Canon 96.6mm (3.8 in.)* for Nikon 94.1mm (3.7 in.)*
Maximum Aperture	F/3.5-6.3	Weight	400g (14.1 oz.)*
Angle of View (diagonal)	75°33' - 7°59'	Aperture Blades	7 (circular diaphragm)*2
Optical Construction	16 elements in 14 groups	Minimum Aperture	F/22-40
Minimum Object Distance	0.49~0.77m (19.3~30.3 in.)	Standard Accessories	Flower-shaped lens hood, Lens caps
Max. Magnification Ratio	1:4 (at f=200mm; MOD 0.5m)	Compatible Mounts	Canon, Nikon, Sony*3
Filter Size	Φ62mm		

[B018 Optical Construction]
■ Hybrid Aspherical Element
■ LD Element



Specifications, appearance, functionality, etc. are subject to change without prior notice.

*Length and weight are based on figures for the Canon and Nikon-mount lens. *2 The circular diaphragm stays almost perfectly circular up to two stops down from maximum aperture.

*1 Length is the distance from the front tip of the lens to the lens mount face. *3 The Sony mount version does not include VC because Sony DSLR bodies incorporate built-in image stabilization.

⚠ Caution: Please read the instruction manual carefully before using the lens.

B18-EG-111-I-1506-0000

TAMRON

Manufacturer of precise and sophisticated optical products for a broad range of industries.

TAMRON CO., LTD.
 1385, Hasunuma, Minuma-ku, Saitama-shi, Saitama 337-8556 JAPAN
 Tel. +81-48-684-9339 Fax. +81-48-684-9349
<http://www.tamron.com>



Management on Quality and Environment

Tamron is certified with international standards: ISO 9001 for quality and ISO 14001 for environmental management at its headquarters, domestic sales offices, China plant as well as its three production facilities in Aomori, Japan, and is fully committed to striving for continued and sustainable improvement at all levels and facets of its business operations.

Note: Information valid as of June 2015. Information in this publication is subject to change at any time without prior notice.