

IP/CCTV LENS NEWS from TAMRON

New Release

High-Resolution

2 Mega-Pixel Fixed-Focal Lens for FA/Machine Vision

■ 1/1.8" 6mm F/1.4 (Model M118FM06) ■ 1/1.8" 12mm F/1.4 (Model M118FM12)



Model		M118FM06	M118FM12	
Imager Size		1/1.8"		
Mount Type		С		
Focal Length		6mm	12mm	
Aperture Range		F/1.4~16		
Field of View Angle	1/1.8"	66.1°∼50.8°	34.2°~25.8°	
(Horizontal×Vertical)	1/2"	58.9°∼44.9°	30.2°∼22.7°	
	1/3"	44.9°~34.0°	22.7°~17.1°	
Focusing Range		0.1m~ ∞		
Operation	Focus	Manual w/Lock		
	Iris	Manual w/Lock		
Filter Size		M34 P=0.5mm	M25.5 P=0.5mm	
Wave Length		Visible Light		

Main Feature

> Higher Quality in Image Capture at Close Distance Range

- Further improvement in image quality at closer distance range most commonly used.
- MOD of 0.1m remains unchanged.

> Sophisticated Optical Design to Boost High Image Quality

- Maximizing performance of 2MP FA/Machine Vision cameras.
- Distinguished uniformity in resolution and contrast from center to corner due to the latest optical design technology.
- Compact form factor.

Easier Installation

O Three positions provided for the locking screw locations (focus and iris respectively) for ease of installation.

> High-Precision, High-Quality Mechanical Construction

- Designated optical design performance ensured with high-precision components manufactured with advanced process technology.
- O Robust construction employed for the core structural barrel components and lens fixing mechanism to maintain performance even in environments with persistent vibration.



Caution: Please read the instruction manual carefully before using the camera.

TAMRON CO., LTD. http://www.tamron.biz/en/1385, Hasunuma, Minuma-ku, Saitama-shi, Saitama 337-8556 JAPAN Tel: +81-48-684-9129 Fax: +81-48-683-8594 E-mail:tokki@tamron.co.jp

TAMRON USA, INC. http://www.tamron-usa.com
10 Austin Boulevard, Commack, NY 11725, USA Tel: +1-631-858-8400 Fax: +1-631-543-3963

TAMRON Europe GmbH. http://www.tamron.de
Robert Bosch-Str. 9, 50769 Cologne, GERMANY Tel: +49-221-970325-0 Fax: +49-221-970325-4

TAMRON INDUSTRIES (HONG KONG) LIMITED http://www.tamron.com.hk
Unit 908, 9/F, Elite Centre, 22 Hung To Road, Kwun Tong, Kowloon, Hong Kong Tel: +852-2721-7797 Fax: +852-2620-1631

Unit 908, 9/F, Elite Centre, 22 Hung To Road, Kwun Tong, Kowloon, Hong Kong Tel: +852-2721-7797 Fax: +852-2620-1631 **TAMRON (Russia) LLC.** http://www.tamron.ru

Unikon Business Center 5F No. 9, Plekhanova Street 4a, Moscow, 111123, Russian Federation
Tel: +7-495-970-0112 Fax: +7-495-970-0112

TAMRON INDIA PRIVATE LIMITED http://www.tamron.in 801, 8th Floor, Time Tower, M.G Road, Sector-28, Gurgaon-122002, Haryana, India Tel: +91-124-41-168-12 Fax: +91-124-40-822-72



Management on Quality and Environment :

Tamron is certified with international standards: ISO 9001 for quality and ISO 14001 for environmental management at its headquarters, domestic sales offices, China plant as well as three production facilities in Aomori, Japan, and is fully committed to striving for continued and sustainable improvement at all levels and facets of its business operations.



Full Line up of 1/1.8" Mega-pixel Lens

Model		M118FM06	M118FM08	M118FM12	
		NEW		NEW	
Imager Size		1/1.8"			
Mount Type		С			
Focal Length		6mm	8mm	12mm	
Aperture Range		F/1.4 ~ 16			
Field of View Ange (Horizontal × Vertical)	1/1.8"	66.1°∼ 50.8°	50.8°∼ 38.6°	34.2°∼ 25.8	
	1/2"	58.9°∼ 44.9°	45.0°∼ 34.0°	30.2°∼ 22.7	
	1/3"	44.9°~ 34.0°	34.0°∼ 25.6°	22.7°~ 17.1°	
Focusing Range		0.1m ~∞			
Operation	Iris	Manual w/Lock			
	Focus	Manual w/Lock			
Filter Size		M34 P=0.5mm	M25.5 P=0.5mm	M25.5 P=0.5mm	
Wave Length	Length Visible Light				

Model		M118FM16	M118FM25	M118FM50	
Imager Size			1/1.8"		
Mount Type		С			
Focal Length		16mm	25mm	50mm	
Aperture Range		F/1.4 ~ 16	F/1.6 ~ 16	F/2.8 ~ 22	
Field of View Ange (Horizontal × Vertical)	1/1.8"	25.9°∼ 19.5°	16.6°∼ 12.5°	8.3°∼ 6.2°	
	1/2"	22.8°~ 17.1°	14.6°∼ 11.0°	7.3°∼ 5.5°	
	1/3"	17.1°∼ 12.9°	11.0°∼ 8.2°	5.5°∼ 4.1°	
Focusing Range		0.1m ~∞		0.2m ~∞	
Operation	Iris	Manual w/Lock			
	Focus	Manual w/Lock			
Filter Size		M25.5 P=0.5mm	M25.5 P=0.5mm	M25.5 P=0.5mm	
Wave Length		Visible Light			